



# HSF

Recommended P.C.B Layout(Top Side)  
(PCB BOARD TOLERANCE±0.05)

**NOTES:**

Current Rating:1.5AMP  
Contact Resistance:20mΩ max  
Withstand Voltage:500V AC/DC  
Insulation Resistance:1000MΩ min  
Operation Temperature:-40°C to +105°C



Contact Material:Brass  
Contact plating:Au or Sn Over Ni  
Insulator Material:PA9T+33%GF(UL94V-0)



## Ordering Information

3111-XX R XX B K00 X 1

No.of Pins	Contact Plating	Color Insulator	Packing
10 30	G0=Gold Flash	B=Black	T=Tube
14 34	G1=3u"Gold		
16 40	G2=5u"Gold		
20 44	G3=10u"Gold		
24 54	G4=15u"Gold		
26 60	G5=30u"Gold		
	S0=Gold Flash/Tin		
	S1=3u"Gold/Tin		
	S2=5u"Gold/Tin		
	S3=10u"Gold/Tin		
	S4=15u"Gold/Tin		
	S5=30u"Gold/Tin		
	SN=Tin		



Item	Contact Length	Mating
Standard	4.00	5222 5224 5225
Alternate		

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	OPERATION		DRAW Tsingsn	DATE 2012/05/31	SCALE UNIT SIZE SHEET PROJ.	FIT mm linch A4 1/1	PART NO. 3111-XXRXXBK00X1
				X.X	±0.40					
				X.XX	±0.25	CHECK	DATE			TITLE: 2.00 BOX HEADER 90° H=5.7
A0	2012/05/31	NEW		X.XXX	±0.15	APPROVE	DATE			Customer NO.
				Angle	± 3'					
				DIM	TOL					

# WCON

Http: www.wcon.com

WCON-Dongguan Tel: +86 769 85358920 Fax: +86 769 85358915 E-mail: sales@wcon.com  
WCON-Kunshan Tel: +86 512 57468408 Fax: +86 512 57468468 E-mail: salesks@wcon.com