



白色小标签

NO4: 将卷盘套上PE-33防水袋,放入1包干燥剂,真空机封口后装入内箱,用封箱胶封装好,贴上标签。



NO5: 将内箱放入外箱，封箱打包，并贴上标签。（3内箱/外箱）



Pin	载带料号	W	S	F	PCS/Reel	PCS/内箱	PCS/外箱
10P	TR3230-10G4401	44.0±0.30	40.40±0.10	20.20±0.15	300	600	1800
12P	TR3230-12G4401	44.0±0.30	40.40±0.10	20.20±0.15	300	600	1800
14P	TR3230-14G4401	44.0±0.30	40.40±0.10	20.20±0.15	400	800	2400
16P	TR3230-16G4401	44.0±0.30	40.40±0.10	20.20±0.15	350	700	2100
20P	TR3230-MN020M11101	56.0±0.30	52.40±0.10	26.20±0.15	350	350	1050
24P	TR3230-MN024M11101	56.0±0.30	52.40±0.10	26.20±0.15	350	350	1050
26P	TR3230-26G5602	56.0±0.30	52.40±0.10	26.20±0.15	300	600	1800
28P	TR3230-MN028M11101	56.0±0.30	52.40±0.10	26.20±0.15	350	350	1050
30P	TR3230-30G5601	56.0±0.30	52.40±0.10	26.20±0.15	350	350	1050
34P	TR3230-MN034M11101	56.0±0.30	52.40±0.10	26.20±0.15	350	350	1050
40P	TR3230-40G5601	56.0±0.30	52.40±0.10	26.20±0.15	350	350	1050
44P	TR3230-MN044M11101	72.0±0.30	68.40±0.10	34.20±0.15	350	350	1050
50P	TR3230-50G7201	72.0±0.30	68.40±0.10	34.20±0.15	350	350	1050
60P	TR3230-MN060M11101	72.0±0.30	68.40±0.10	34.20±0.15	350	350	1050
64P	TR3230-64G8801	88.0±0.30	84.40±0.10	42.20±0.15	350	350	1050
70P	TR3230-MN070M11101	88.0±0.30	84.40±0.10	42.20±0.15	350	350	1050
80P	TR3230-MN080M11101	88.0±0.30	84.40±0.10	42.20±0.15	350	350	1050
88P	TR3230-MN088M11101	104.0±0.30	100.40±0.10	50.20±0.15	350	350	1050

					工 程 图 ENGINEERING		绘图 DRAW	刘胜	2019/05/24	SCALE	Fit
						X.X	±0.30	设计 DESIGN		UNIT	mm
						X.XX	±0.20			SIZE	A4
						X.XXX	±0.10			SHEET	1/1
A0	2019/05/24	NEW	-----	-----		Angle	± 2'	核 准 CHECK			
版次 REV	日期 DATE	变 更 说 明 MODIFICATION DESCRIPTION	变 更 CHANGE	核 准 APPROVE		DIM	TOL	核 准 APPROVE		PROJ.	

WCON Hardware Electronics Co., Ltd

品名 TITLE:	1.27mm简牛 ,SMT,Short Latch, W/T CAP,L=7.8/5.6(0)/2.8 卷装规范
-----------	---